



# EnerShed SM

## Energy Storage System

**Rated AC Output Power: 60 kVA - 150 kVA**

**Capacity: 260 kWh - 430 kWh**



**EnerShed SM**  
150 kVA/500 kWh  
= 150 kWh/m<sup>2</sup>



**Competitor A**  
150 kW / 372 kWh  
= 79.5 kWh/m<sup>2</sup>



**Competitor B**  
125 kW / 279.5 kWh  
= 99.3 kWh/m<sup>2</sup>

### General Specifications

Model	EnerShed 60		EnerShed 90		EnerShed 120		EnerShed 150	
Rated AC Output Power	60 kVA		90 kVA		120 kVA		150 kVA	
Capacity*	100 kWh	200 kWh	150 kWh	300 kWh	200 kWh	400 kWh	250 kWh	500 kWh
Rated AC Current	72.5 A (PF=1)		108.8A (PF=1)		145.0 A (PF=1)		181.3 A (PF=1)	
Max Continuous AC Current	76.0 A (PF=1)		114.0 A (PF=1)		152.0 A (PF=1)		190 A (PF=1)	
Cycle Life	80% SoH @ 4000 cycles, 25C							
System Weight	2,295 kg (5,049 lbs)	2,905 kg (6,391 lbs)	2,625 kg (5,797 lbs)	3,670 kg (8,074 lbs)	2,985 kg (6,567 lbs)	4,435 kg (9,757 lbs)	3,345 kg (7,374 lbs)	5,200 kg (11,440 lbs)
Regulatory	UL9540, UL9540A, UL1741 SA/SB, IEEE 1547-2020, UL1642, UL1973							

### Operating and Mechanical Data

Dimensions (H x D x W)	114" x 87" x 59"
Enclosure	Nema 3R
Corrosion Category IEC 61701	C5
Cooling	Forced Air
Operating Temperature Range	-30 C - 60 C
Storage Temperature Range	5 C to 40 C
Maximum Permissible Relative Humidity	95%
Rated Altitude	3000 ft
Noise Emission	65 dB(A)
FCC	Class A

### Electrical Data

Nominal AC voltage / Line Connection	480 Vac / 3-phase Wye
Grid Frequency	60 Hz
Harmonics (THD)	<5%
PF at rated power / displacement	1 / 0.8 Leading - 0.8 Lagging
Communication	SunSpec over ModBus TCP/IP

\*Nominal usable energy at AC terminals, Day 1. Consult with Myers for additional power and capacity sizes not shown here.



# EnerShed MD

## Energy Storage System

**Rated AC Output Power: 270 kVA**  
**Capacity: 515 kWh - 775 kWh**



**EnerShed MD**  
 270 kVA/900 kWh  
 = 108 kWh/m<sup>2</sup>



**Competitor A**  
 250 kW / 1000 kWh  
 = 67 kWh/m<sup>2</sup>



**Competitor B**  
 250 kW / 930 kWh  
 = 95.4 kWh/m<sup>2</sup>

### General Specifications

Model	<b>EnerShed 180</b>		<b>EnerShed 210</b>		<b>EnerShed 240</b>		<b>EnerShed 270</b>	
Rated AC Output Power	180 kVA		210 kVA		240 kVA		270 kVA	
Capacity*	300 kWh	600 kWh	350 kWh	700 kWh	400 kWh	800 kWh	450 kWh	900 kWh
Rated AC Current	217.5 A (PF=1)		253.8 A (PF=1)		290.0 A (PF=1)		326.3 A (PF=1)	
Max Continuous AC Current	228.0 A (PF=1)		266.0 A (PF=1)		304.0 A (PF=1)		342.0 A (PF=1)	
Cycle Life	80% SoH @ 4000 cycles, 25C							
System Weight	6,525 kg (14,387 lbs)	8,955 kg (19,745 lbs)	6,885 kg (15,181 lbs)	9,270 kg (21,432 lbs)	7,245 kg (15,975 lbs)	10,485 kg (23,119 lbs)	7,605 kg (16,769 lbs)	11,250 kg (24,806 lbs)
Regulatory	UL9540, UL9540A, UL1741 SA/SB, IEEE 1547-2020, UL1642, UL1973							

### Operating and Mechanical Data

Dimensions (H x D x W)	79" x 129" x 100"
Enclosure	Nema 3R
Corrosion Category IEC 61701	C5
Cooling	Forced Air
Operating Temperature Range	-30 C - 60 C
Storage Temperature Range	5 C to 40 C
Maximum Permissible Relative Humidity	95%
Rated Altitude	3000 ft
Noise Emission	65 dB(A)
FCC	Class A

### Electrical Data

Nominal AC voltage / Line Connection	480 Vac / 3-phase Wye
Grid Frequency	60 Hz
Harmonics (THD)	<5%
PF at rated power / displacement	1 / 0.8 Leading - 0.8 Lagging
Communication	SunSpec over ModBus TCP/IP

\*Nominal usable energy at AC terminals, Day 1. Consult with Myers for additional power and capacity sizes not shown here.



# EnerShed LG

## Energy Storage System

**Rated AC Output Power: 570 kVA - 1170 kVA**

**Capacity: 1,115 kWh - 4,770 kWh**



**EnerShed LG**  
570 kVA/1900 kWh  
= 228 kWh/m<sup>2</sup>



**Competitor A**  
250 kW / 1000 kWh  
= 67 kWh/m<sup>2</sup>



**Competitor B**  
1.5 kW / 3720 kWh  
= 194 kWh/m<sup>2</sup>

### General Specifications

Model	EnerShed 330		EnerShed 390		EnerShed 450		EnerShed 510		EnerShed 570	
Rated AC Output Power	330 kVA		390 kVA		450 kVA		510 kVA		570 kVA	
Capacity*	550 kWh	1,100 kWh	650 kWh	1,300 kWh	750 kWh	1,500 kWh	850 kWh	1,700 kWh	950 kWh	1,900 kWh
Rated AC Current	398.8 A (PF=1)		471.3 A (PF=1)		543.8 A (PF=1)		616.3 A (PF=1)		688.8 A (PF=1)	
Max Cont. AC Current	418.0 A (PF=1)		494.0 A (PF=1)		570.0 A (PF=1)		646.0 A (PF=1)		722.0 A (PF=1)	
Cycle Life	80% SoH @ 4000 cycles, 25C									
System Weight	18,500 kg (40,793 lbs)	22,955 kg (50,616 lbs)	19,220 kg (42,380 lbs)	24,485 kg (53,989 lbs)	19,940 kg (43,968 lbs)	26,015 kg (57,363 lbs)	20,660 kg (45,555 lbs)	27,545 kg (60,737 lbs)	21,380 kg (47,143 lbs)	29,075 kg (64,110 lbs)
Regulatory	UL9540, UL9540A, UL1741 SA/SB, IEEE 1547-2020, UL1642, UL1973									

### Operating and Mechanical Data

Enclosure	Nema 3R
Corrosion Category IEC 61701	C5
Cooling	Forced Air
Operating Temperature Range	-30 C - 60 C
Storage Temperature Range	5 C to 40 C
Maximum Permissible Relative Humidity	95%
Rated Altitude	3000 ft
Noise Emission	65 dB(A)
FCC	Class A

### Electrical Data

Nominal AC voltage / Line Connection	480 Vac / 3-phase Wye
Grid Frequency	60 Hz
Harmonics (THD)	<5%
PF at rated power / displacement	1 / 0.8 Leading - 0.8 Lagging
Communication	SunSpec over ModBus TCP/IP

\*Nominal usable energy at AC terminals, Day 1. Consult with Myers for additional power and capacity sizes not shown here.